

## 2024 Valcke Bronzen Schietspoel



Oil Pattern Distance **Forward Oil Total Tank Configuration** 

43 19.9 mL Multi Tank

**Reverse Brush Drop Reverse Oil Total Tank A Conditioner** 

38 7 mL **Terrain**  Oil Per Board **Volume Oil Total Tank B Conditioner** 

50 ul 26.9 mL Ice

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	6	18	4	Α	222	0.0	12.7	12.7	11100
2	6L	6R	2	18	3	Α	58	12.7	17.8	5.1	2900
3	9L	9R	2	18	3	Α	46	17.8	22.9	5.1	2300
4	10L	10R	2	18	3	Α	42	22.9	28.0	5.1	2100
5	12L	12R	1	18	3	Α	17	28.0	30.5	2.5	850
6	14L	14R	1	18	3	Α	13	30.5	33.0	2.5	650
7	2L	2R	0	22	3	Α	0	33.0	37.0	4.0	0
8	2L	2R	0	26	3	Α	0	37.0	43.0	6.0	0

1   2L   2R   0   30   3   B   0   43.0   29.0   -14.0   0     2   16L   16R   1   22   3   B   9   29.0   25.9   -3.1   450     3   14L   14R   2   18   3   B   26   25.9   20.8   -5.1   1300     4   13L   13R   2   18   3   B   30   20.8   15.7   -5.1   1500     5   12L   12R   1   18   3   B   17   15.7   13.2   -2.5   850     6   10L   10R   1   14   3   B   21   13.2   11.3   -1.9   1050     7   2L   2R   1   14   4   B   37   11.3   9.4   -1.9   1850     8   2L   2R   0   14   4   B   0   9.4   0.0   -9.4   0		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 14L 14R 2 18 3 B 26 25.9 20.8 -5.1 1300   4 13L 13R 2 18 3 B 30 20.8 15.7 -5.1 1500   5 12L 12R 1 18 3 B 17 15.7 13.2 -2.5 850   6 10L 10R 1 14 3 B 21 13.2 11.3 -1.9 1050   7 2L 2R 1 14 4 B 37 11.3 9.4 -1.9 1850	1	2L	2R	0	30	3	В	0	43.0	29.0	-14.0	0
4 13L   13R   2 18   3 B   30 20.8 15.7 -5.1 1500     5 12L   12R   1 18   3 B   17 15.7 13.2 -2.5 850     6 10L   10R   1 14   3 B   21 13.2 11.3 -1.9 1050     7 2L   2R   1 14   4 B   37 11.3 9.4 -1.9 1850	2	16L	16R	1	22	3	В	9	29.0	25.9	-3.1	450
5 12L 12R 1 18 3 B 17 15.7 13.2 -2.5 850   6 10L 10R 1 14 3 B 21 13.2 11.3 -1.9 1050   7 2L 2R 1 14 4 B 37 11.3 9.4 -1.9 1850	3	14L	14R	2	18	3	В	26	25.9	20.8	-5.1	1300
6 10L 10R 1 14 3 B 21 13.2 11.3 -1.9 1050 7 2L 2R 1 14 4 B 37 11.3 9.4 -1.9 1850	4	13L	13R	2	18	3	В	30	20.8	15.7	-5.1	1500
7 2L 2R 1 14 4 B 37 11.3 9.4 -1.9 1850	5	12L	12R	1	18	3	В	17	15.7	13.2	-2.5	850
	6	10L	10R	1	14	3	В	21	13.2	11.3	-1.9	1050
8 2L 2R 0 14 4 B 0 9.4 0.0 -9.4 0	7	2L	2R	1	14	4	В	37	11.3	9.4	-1.9	1850
	8	2L	2R	0	14	4	В	0	9.4	0.0	-9.4	0

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 650 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



	I			<u> </u>		
Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	2.82	1,72	1.06	1.06	1,72	2.82



